



Safety Data Sheet

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name Tamiya AS Spray Paints (Range of Colours)
Contains Contains Titanium dioxide, Butyl acetate, Methyl isobutyl ketone, Butanol
U.F.I.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Aerosolised synthetic spray paints for model and hobby crafts

1.3. Details of the supplier of the safety data sheet

Name: The Hobby Company Ltd (*HobbyCo Ltd*)

Address: Garforth Place
Knowlhill
Milton Keynes
MK5 8PG

Telephone: +44 (0)1908 605 686

Email: service@hobbyco.net

1.4. Emergency telephone

For Great Britain:

111 for non-emergencies
999 for life-threatening emergencies

For Northern Ireland:

Telephone your GP for non-emergencies (during working hours)
Outside working hours, use the number for your area in the table below:

Area/town	Telephone
North and West Belfast	028 9074 4447
South and East Belfast	028 9079 6220
Ards and North Down	028 9182 2344
Lisburn and Downpatrick	028 9260 2204
Antrim	028 2566 3500
Ballymena	
Ballymoney	
Cookstown	
Carrickfergus	
Coleraine	
Larne	
Magherafelt	
Moyle	
Newtownabbey council areas	

Area/town	Telephone
Armagh and Dungannon Craigavon and Banbridge	028 3839 9201
Newry and Mourne	
Enniskillen Omagh Strabane Derry/Londonderry Limavady	028 7186 5195

999 for life-threatening emergencies

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol Category 1, H222, H229

Skin Irritation Category 2, H315

Eye Irritation Category 2, H319

Specific Target Organ Toxicity Single Exposure Category 3, H336

Carcinogen Category 2, H351

2.2. Label elements

Pictograms:



Signal Word: Danger

Hazard Statements:

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary Statements:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep out of the reach of children. Keep away from sources of ignition - No smoking. Use only outdoors or in a well-ventilated area

Supplemental information on the label:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Label information where small pack derogation applies (<125ml):

Pictograms:



Signal Word: Danger

Hazard Statements:

Extremely flammable aerosol. Pressurised container: May burst if heated. May cause drowsiness or dizziness. Suspected of causing cancer.

Precautionary Statements:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Keep out of the reach of children. Read label before use. Keep away from sources of ignition - No smoking. Use only outdoors or in a well-ventilated area

Supplemental information on the label:

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3. Other hazards

Does not contain substances known to be endocrine disrupting to humans or the environment

Product presents an inhalation risk in spray form, or if dried and flaked into respirable dust particles

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Substance name	Identification numbers (CAS, EC, Index)	% w/w or % v/v	REACH reg. no	CLP Classification	M-factors, SCLs, ATEs	Notes
Methyl isobutyl ketone	108-10-1	5.00%-10.00%		Flam. Liq. 2; H225 Eye Irrit. 2; H319 Acute Tox. 4; H332 STOT SE 3; H336 Carc. 2; H351i		*
Butyl cellosolve	111-76-2	1.00%-5.00%		Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Acute Tox. 4; H332		*
Dimethyl ether	115-10-6	40.00%-70.00%		Flam. Gas 1; H220 Press. Gas (Comp.); H280		*
Butyl acetate	123-86-4	1.00%-		Flam. Liq. 3; H226		*

		10.00%		STOT SE 3; H336 EUH018		
Iso-amyl acetate	123-92-2	1.00%- 10.00%		Flam. Liq.: 3; H226		*
C.I. Pigment Red 101	1309-37-1	0.01%- 1.00%		not classified		*
C.I. Pigment Black 7	1333-86-4	0.01%- 1.00%		not classified		*
C.I. Pigment White 6	13463-67-7	0.10%- 5.00%		classified H351i in powder form containing 1 % or more of particles with aerodynamic diameter $\leq 10 \mu\text{m}$;		Note 10 Note W *
C.I. Pigment White 21	7727-43-7	0.01%- 1.00%		not classified		*
Solvent naphtha	64742-95-6	0.10%- 0.99%		Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Muta. 1B; H340 Carc. 1B; H350 Repr. 2; H361f Aquatic Chronic 2; H411		
Acetone	67-64-1	1.00%- 5.00%		Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336		*
Aluminium	7429-90-5	0.10%- 5.00%		Flam. Sol. H228 Water-react; H261		*
Iso-butanol	78-83-1	5.00%- 9.99%		Flam. Liq. 3; H226 Skin Irrit. 2; H315 Eye Dam. 1; H318 STOT SE 3; H335 STOT SE 3 H336		*

*Substances with an occupation exposure limit. For further information, see section 8.1.

Note 10 - The classification as a carcinogen by inhalation applies only to mixtures in powder form containing 1 % or more of titanium dioxide which is in the form of or incorporated in particles with aerodynamic diameter $\leq 10 \mu\text{m}$.

Note W - It has been observed that the carcinogenic hazard of this substance arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung. This note aims to describe the particular toxicity of the substance; it does not constitute a criterion for classification according to this Regulation.

For the full text of H-Statements referred to under Sections 2 and 3 of the SDS, see Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

If inhaled aerosol or sprayed material, remove immediately to fresh air. If breathing is difficult, get immediate medical attention. Keep afflicted person awake, warm and at rest. Properly trained persons may administer oxygen.

If in contact with skin, wash immediately with soap and water. Wash contaminated clothing before reuse. If symptoms occur, seek medical attention.



In case of contact with eyes, immediately flush with water for at least 20 minutes. Remove contact lenses (if present) and continue rinsing. Get medical attention.
If swallowed DO NOT INDUCE VOMITING. Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Seek medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation of dust or spray will cause coughing wheezing and shortness of breath. Use in poorly ventilated or enclosed areas may result in drowsiness, dizziness, headaches, confusion and nausea. Contact with skin and eyes will cause redness, rash, itching and discomfort.

Intentional misuse or overexposure to aerosols may be harmful or fatal.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Use water fog, dry chemical or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

Aerosols are extremely flammable. In the event of a fire, aerosol spray containers may become over-pressurised and rupture releasing flammable contents. Vapours may ignite explosively creating fireballs and/or flaming missiles spreading the fire over a greater area. Ruptured containers may become projectiles or shrapnel.

Containers should be kept cool in the event of a fire. Do not spray on or near naked flames. Do not pierce or burn aerosols, even after use. Dispose of containers correctly (see section 13).

Users should note that paint accessories, brushes, cloths etc... should also be considered flammable once used.

Combustion products will include carbon monoxides and carbon dioxides.

5.3. Advice for firefighters

In the event of fire, wear appropriate protective equipment and self-contained breathing apparatus (SCBA). Firefighter clothing must conform to a minimum standard of EN469 including helmets, protective boots and gloves. Use shielding to protect against rupturing containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Do not touch or walk through spilled material. Keep unnecessary persons away from the spillage. Prevent inhalation of spray, or creation of dusts/flakes of dried material. Use appropriate personal protective equipment to prevent direct contact with the material.

Emergency personnel should take into account the volume of the spillage and the likelihood of direct contact when selecting appropriate personal protective equipment. Do not breath mists or sprays.



6.2. Environmental precautions

Keep spills away from drains, surface water, groundwater, wells and boreholes or other infrastructure which may allow spills into groundwater.

6.3. Methods and material for containment and cleaning up

Stop leak if safe to do so. Absorb spillage with inert dry material such as sand, earth or vermiculite and place in an appropriate non-flammable waste disposal container, avoiding the creation of dusts or respirable particulates. Dispose of via a licensed disposal contractor. Do not place into domestic waste. Do not flush into drains or watercourses.

6.4. Reference to other sections

See section 8 for information on personal protective equipment
See section 13 for additional waste disposal information

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Wash thoroughly after handling. Take off contaminated clothing and wash it before reuse. Do not breathe spray or mists. Do not eat drink or smoke whilst handling product. If product has dried, minimise flaking or creation of dusts and fine particulates.

If sanding models which have been painted with this product, wear a dust mask with particulate filter to prevent inhalation of dusts.

7.2. Conditions for safe storage, including any incompatibilities

Store in the original container. Store upright to prevent spills or leakage. Do not tamper or attempt to open the spray fitting.

Do not pierce or burn empty containers.

Store out of direct sunlight. Do not freeze.

7.3. Specific end use(s)

Hobby/Craft synthetic paint for spray application. Supplied in aerosol containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Workplace or Occupational Exposure Limits

UK Workplace Exposure Limits (EH40)

Substance	CAS #	Short Term Exposure Limit (STEL)	Long Term Exposure Limit (TWA)	Notes
Methyl isobutyl ketone	108-10-1	100 ppm 416 mg/m ³	50 ppm 208 mg/m ³	(skin)



Butyl cellosolve	111-76-2	50 ppm 246 mg/m ³	25 ppm 123 mg/m ³	(skin)
Dimethyl ether	115-10-6	500 ppm 958 mg/m ³	400 ppm 766 mg/m ³	
Butyl acetate	123-86-4	200 ppm 966 mg/m ³	150 ppm 724 mg/m ³	
CI Pigment Red 101	1309-37-1	10 mg/m ³	5 mg/m ³	
CI Pigment Black 7	1333-86-4	7 mg/m ³	3.5 mg/m ³	
CI Pigment White 6	13463-67-7		10 mg/m ³ (Inhalable) 4 mg/m ³ (Respirable)	
CI Pigment White 21	7727-43-7		10 mg/m ³ (Inhalable) 4 mg/m ³ (Respirable)	
Acetone	67-64-1	1500 ppm 3620 mg/m ³	500 ppm 1210 mg/m ³	
Aluminium	7429-90-5		10 mg/m ³ (Inhalable) 4 mg/m ³ (Respirable)	
Iso-Butanol	78-83-1	75 ppm 231 mg/m ³	50 ppm 154 mg/m ³	

UK Biological Monitoring Guidance Values

Substance	CAS #	Monitoring Guidance
Methyl isobutyl ketone	108-10-1	20 µmol substance/L in urine post-shift
Butyl cellosolve	111-76-2	240 mmol butoxyacetic acid/mol creatinine in urine post-shift

European Union Workplace Exposure Limits

Substance	CAS #	Short Term Exposure Limit (STEL)	Long Term Exposure Limit (TWA)	Notes
Methyl isobutyl ketone	108-10-1	50 ppm 208 mg/m ³	20 ppm 83 mg/m ³	
Butyl cellosolve	111-76-2	50 ppm 246 mg/m ³	20 ppm 98 mg/m ³	(skin)
Dimethyl ether	115-10-6		1000 ppm 1920 mg/m ³	
Butyl acetate	123-86-4	150 ppm 723 mg/m ³	50 ppm 241 mg/m ³	
Iso-amyl acetate	123-92-2	100 ppm 550 mg/m ³	50 ppm 270 mg/m ³	
Acetone	67-64-1		500 ppm 1210 mg/m ³	

8.2. Exposure controls

Use outdoors or in a well ventilated area. If ventilation is inadequate and/or exposure exceeds the workplace exposure limits then local exhaust ventilation and respiratory protection should be used.



When using respiratory protection, the recommendation is a combination particulate filter and organic vapour filter.

Clothing should be washed before reuse. If prolonged skin contact is expected, glove use may be advisable. Recommended glove material – Nitrile rubber, thickness 3mm. Instructions and information provided by the manufacturer on storage, maintenance and replacement must be followed to ensure protection and effectiveness.

This glove type may not be appropriate for all conditions and environments. It is recommended to obtain independent professional advice and complete a risk assessment specific to your application and working environment. The user must check that the final glove choice is suitable.

Whilst spraying, users should wear appropriate eye protection such as safety glasses with side shields. Never spray into the wind.

Always handle in accordance with good safety practice and hygiene. Do not eat, drink or smoke whilst handling product. Wash hands thoroughly after use.

Prevent build up of vapours by opening doors and windows. If you become light headed, nauseous or drowsy at any time whilst using the product, immediately cease use and move to fresh air. Overexposure to aerosols can be harmful or fatal.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Aerosol

Colour: Each paint is an individual colour, see product label

Odour and odour threshold: Odour of ketones

Melting point/ freezing point: Not determined

Boiling point, or initial boiling point and boiling range: -24 °C

Flammability (if solid or gas): Not determined

Lower and upper flammability or explosive limits: 2.8 – 24.4 Vol. %

Flash point: -40 °C

Auto-ignition temperature: Not determined

Decomposition temperature: Not determined

pH: Not determined

Kinematic viscosity: Not determined

Solubility: Not determined

Partition coefficient: n-octanol/water: Not determined

Vapour pressure: Not determined

Relative density: 1.63



Relative vapour density: Not determined

Particle characteristics: Not determined

9.2. Other information

No additional information

SECTION 10: Stability and reactivity

10.1. Reactivity

No relevant information

10.2. Chemical stability

The product is stable when stored at normal ambient temperatures.

10.3. Possibility of hazardous reactions

In use may form flammable/explosive vapour-air mixtures

10.4. Conditions to avoid

Avoid high temperatures and direct sunlight.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

There are no known hazardous decomposition products in normal use

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation EC No 1272/2008

Acute toxicity

Based on the available data, the classification criteria have not been met

Irritation/ Corrosion

On the basis of calculation method, the product is classified as irritating to skin and eyes

Product/ingredient name	Target and result	Species	Score	Exposure	Observation
iso-Butanol	OECD Guideline 405	Rabbit	-	24 hours	Corrosive, not all parameters fully reversable in 14 days
Methyl isobutyl ketone	OECD guideline 405	Rabbit	-	Single exposure	Fully reversable



Sensitisation

Based on the available data, the classification criteria have not been met

Mutagenicity

Based on the available data, the classification criteria have not been met

Carcinogenicity

On the basis of calculation method, the product is suspected of causing cancer

Product/ingredient name	Test	Experiment	Result
Methyl isobutyl ketone	OECD guideline 451	Inhalation, Vapour	Carcinogenic effects in rats: liver/kidneys
Titanium dioxide	No guideline followed	Oral	No tumours related to TiO ₂

Reproductive toxicity

Based on the available data, the classification criteria have not been met

Specific target organ toxicity (single exposure)

On the basis of calculation method, the product may cause narcotic effects including drowsiness and dizziness.

Product/ingredient name	Category	Route of exposure	Target organs
Butyl Acetate	Category 3	Inhalation	Narcotic effect
Iso-butanol	Category 3	Inhalation	Narcotic effect
Iso-butanol	Category 3	Inhalation	Respiratory System

Specific target organ toxicity (repeated exposure)

Based on available data the classification criteria have not been met

Aspiration hazard

Based on available data the classification criteria have not been met

11.2. Information on other hazards

This product does not contain constituents known to cause endocrine disruption to human health

Intentional misuse or overexposure to aerosols may be harmful or fatal.

SECTION 12: Ecological information

12.1. Toxicity

Based on the available data the classification criteria have not been met

12.2. Persistence and degradability

This product has not been tested for its persistence and degradability



12.3. Bioaccumulative potential

This product has not been tested for its bioaccumulative potential

12.4. Mobility in soil

Not determined

12.5. Results of PBT and vPvB assessment

This product does not contain substances known to be Persistent, Bioaccumulative and Toxic, or Very Persistent and Very Bioaccumulative.

12.6. Endocrine disrupting properties

This product does not contain substances known to cause endocrine disruption to the environment

12.7. Other adverse effects

No other information known on other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste generation should be avoided or minimised where possible. Surplus, unused products should be sold or returned to the manufacturer, if possible, for beneficial use or recycling. Product disposal to sewer should be avoided, if possible, and only be carried out after treatment, and under relevant rules, e.g. Consent to Discharge.

Where wastes have to be disposed of, use a licenced waste contractor, and obey all national and local rules. Used paint containers should be disposed of at household waste recycling centres whether empty or part filled. Some centres will accept liquid usable paint for recycling schemes. Please check local requirements before disposal. Do not place in household waste. Paint containers (even when empty) cannot be disposed of as household waste.

Do not puncture, pierce or crush used containers.

Used packaging waste should be reused or recycled, if uncontaminated. Contaminated packaging should be cleaned on site, if appropriate facilities exist, including any relevant rules or permits, or offsite by a specialist provider. Contaminated packaging which cannot be safely cleaned must be treated in the same way as the product, and should only be disposed of as a last resort.

SECTION 14: Transport information

	ADR/RID	IMDG	IATA
14.1 UN number or ID number	UN1950	UN1950	UN1950
14.2. UN proper shipping name	AEROSOLS, flammable	AEROSOLS, flammable	AEROSOLS, flammable
14.3. Transport	2.1	2.1	2.1



hazard class(es)			
14.4. Packing group	Not available	Not available	Not available
14.5. Environmental hazards	No	No	No

Additional information

ADR/RID: Tunnel restriction code D
IMDG: EmS F-D, S-U
IATA: ERG Code: 10L

14.6. Special precautions for user

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not intended for bulk transport

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

This SDS has been compiled according to REACH regulation EC 2020/878, and CLP Regulation 1272/2008, as amended.

15.2. Chemical safety assessment

A chemical safety assessment is not required for this mixture

SECTION 16: Other information

Key:

ADR/RID – European Agreement concerning the International Carriage of Dangerous Goods by Road/Rail
IATA – International Air Transport Association
IMDG – International Maritime Dangerous Goods
PBT – Persistent, Bioaccumulative and Toxic Substance
vPvB – Very Persistent and Very Bioaccumulative
EPA – Environmental Protection Agency
OECD – Organisation for Economic Co-Operation and Development
LTEL – Long-term Exposure Limit
STEL – Short-term Exposure Limit
WEL – Workplace Exposure Limit
LC50 – Lethal Concentration to 50% of a test population
LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose)
EC50 – 50% of maximal Effective Concentration

Literature References and Sources for Data: European Chemicals Agency, Health and Safety Executive, Information provided from supply chain.

Full text of H-Statements referred to under Sections 2 and 3 of the SDS:



<i>Flammable Gas Category 1, H220</i>	<i>Extremely flammable gas.</i>
<i>Flammable Liquid Category 2, H225</i>	<i>Highly flammable liquid and vapour.</i>
<i>Flammable Liquid Category 3, H226</i>	<i>Flammable liquid and vapour.</i>
<i>Flammable Solid Category 2, H228</i>	<i>Flammable solid.</i>
<i>Aerosol Category 1, H222, H229</i>	<i>Extremely flammable aerosol. Pressurised container: May burst if heated.</i>
<i>Substances and Mixtures which, in contact with water, emit flammable gases, Category 2, H261</i>	<i>In contact with water releases flammable gases</i>
<i>Gasses Under Pressure (Compressed) Category 1 (H280)</i>	<i>Contains gas under pressure; may explode if heated.</i>
<i>Acute Toxicity Category 4, H302</i>	<i>Harmful if swallowed.</i>
<i>Aspiration Toxicity 1, H304</i>	<i>May be fatal if swallowed and enters airways.</i>
<i>Skin Irritant Category 2, H315</i>	<i>Causes skin irritation.</i>
<i>Eye Damage Category 1, H318</i>	<i>Causes serious eye damage.</i>
<i>Eye Irritant Category 2, H319</i>	<i>Causes serious eye irritation.</i>
<i>Acute Toxicity Category 4, H332</i>	<i>Harmful if inhaled.</i>
<i>Specific Target Organ Toxicity Single Exposure Category 3, H335</i>	<i>May cause respiratory irritation.</i>
<i>Specific Target Organ Toxicity Single Exposure Category 3, H336</i>	<i>May cause drowsiness or dizziness.</i>
<i>Mutagen Category 1B, H340</i>	<i>May cause genetic defects</i>
<i>Carcinogen Category 1B, H350</i>	<i>May cause cancer</i>
<i>Carcinogen Category 2, H351</i>	<i>Suspected of causing cancer</i>
<i>Carcinogen Category 2, H351i</i>	<i>Suspected of causing cancer if inhaled</i>
<i>Reproductive Toxicity Category 2, H361f</i>	<i>Suspected of damaging fertility</i>
<i>Aquatic Chronic Toxicity Category 2, H411</i>	<i>Toxic to aquatic life with long lasting effects</i>
<i>EUH018</i>	<i>In use, may form flammable/explosive vapour-air mixture</i>
<i>EUH211</i>	<i>Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.</i>

ANNEX